Quality:	8600 Porto						
Pile Content:	100% Polyester						
Overall Content:	100% Polyester						
Finish:	Water, Oil, and Stain Repellent						
Backing:	N/A						
Weight:	Imperial	Metric					
	20.0 oz/lyd	620.0 gr/lm					
	13.3oz/sqyd	452.6 gr/m2					
Width:	54 inches						
Average Roll Size:	50 yd						
Application:	Home Furnishings	Χ	Upho	olstery			
Country of Origin:	United States of America	a					
Abrasion:	Wysenbeck Method	Martindale Method					
	250,000 Double Rubs			80,000			
	ASTM D 4157-92	ASTM D4966-10					
Tensile Strength:	Length	100.0 kg		minimum	22.7	kg	(50 lb)
ASTM D5034-95	Width	108 kg		minimum	22.7	kg	(50 lb)
Seam Tensile Strength:	Length	22.0 kg		minimum	11.4	kg	(25 lb)
ASTM D434-95	Width	17.0 kg		minimum	11.4	kg	(25 lb)
Colorfastness:	Xenon	40 hours	4.5		20 hou	rs	NA
	AATCC 16-1993	min	4.0 @	40 hrs		min	NA
	Crocking	Dry		4.5	Wet		4.5
	AATCC 8-1989	min		4.0		min	3.0
Cleaning Code:	S	Professional Clean Only					
Flammability Testing:	UFAC	Class I					
(Performed by a Certified Laboratory)	CAL TB 117-2013	Complies					
	NFPA 260	Class I					